

MISSION-CRITICAL DATA PROTECTION SYSTEMS

















SecureNAS CX-80KSD

Extreme Speed with Encrypted Storage in a Small Durable Package

Supporting eight hot-swappable 2.5" SSDs and up to two internal 2.5" SDDs, the **Ciphertex SecureNAS CX-80KSD** is a high-capacity, rugged, and reliable enterprise NAS powered by an Intel® Xeon® D(4, 8, or 16 Core) processor. Built-in Intel® AES-NI provides integrated support to enable fast and secure data encryption and decryption for a wide range of cryptographic applications, such as bulk encryption/decryption, authentication, random number generation, and authenticated encryption, providing strong security while also reducing performance impact. Designed to optimize enterprise IT infrastructure, the **Ciphertex SecureNAS CX-80KSD** comes with two PCle slots that support 10GbE/40GbE NIC, PCle SSD, as well as graphics cards. Incorporating security and scalability, the **Ciphertex SecureNAS CX-80KSD** presents an ideal choice to accommodate multiple streams of 4K HDR video streaming as well as the high IO required for rendering animations. Secured by rugged enclosure that ensures full military-grade durability, the **Ciphertex SecureNAS CX-80KSD** system also includes a FIPS-certified encryption key that can be used for locking and unlocking encrypted volumes.

Features

- Intel® Xeon® processor D-1518 4-Core, with optional 8 and 16-Core expandability, featuring the latest 14nm energy-efficient SoC
- Dual 10GbE fiber & copper expandability for highlyefficient virtualization and intensive data transmission
- LCD display for real-time information and easier system management
- Compartmentalized smart cooling; detects CPU and hard drive temperatures to dynamically control fan speeds for quieter operation
- High-quality hardware enables optimum performance to fulfill diversified applications

- Hardware accelerated AES-256 bit encryption
- Supports four DDR4 memory modules for a maximum of 128GB RAM
- One built-in M.2 SATA 6GB/s slot to provide the greatest flexibility in tiered storage configuration with native high speeds that empower SSD caching
- Centralized management solution for networked computing devices
- Supports centralized storage, backup, sharing, and disaster recovery
- Optional 5 year warranty (3 years included)

Ciphertex CX-Linux OS Software

The new Ciphertex Linux-based CX-Linux OS, featuring ZFS has the ability to maintain the utmost data integrity. Not only does our OS inherit the amazing native features of ZFS, its powerful features ensure persistent, reliable storage management, protection against data corruption, seamless capacity expansion, several data integrity mechanisms, as well as pool and disk encryption protection.

ORGANIZATIONS WORLDWIDE TRUST THEIR DATA TO CIPHERTEX























SPECIFICATIONS

PERFORMANCE CPU	Intel® Xeon Processor D-1518 Socket FCBGA 1667 supported CPU TDP support 35W
CORES/CACHE	4 Cores (upgradable to 8 and 16 Cores), 8 Threads /6MB Cache
MEMORY CAPACITY	Up to 128GB; Unbuffered ECC/non-ECC UDIMM, DDR4-2133MHz, in 4 DIMM slots
MEMORY TYPE	2133/1866/1600MHz ECC DDR4 ECC RDIMM and ECC/Non-ECC UDIMM
DIMM SIZES	4GB, 8GB, 16GB, 32GB
MEMORY VOLTAGE	1.2V
ERROR DETECTION	Corrects single-bit errors Detects double-bit errors (using ECC memory)
M.2 EXPANSION	M.2 Interface: 1 SATA/PCI-E 3.0 x4
SAS2	Broadcom 2116 SW controller for 16 SATA3 (6Gpbs) ports; SAS2 and SATA3

IPMI Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support Dual LAN with 10G SFP+ from D-1500 SoC; Dual LAN with 1GbE w/Intel® 1210 GRAPHICS Aspeed AST2400 BMC LED INDICATORS Status/Power, USB, LAN PUSH BUTTONS Power, Reset, Copy TEMPERATURE 0 - 60°C (32°F ~ 140°F) SMART FAN 1 x 12cm (12V DC) WEIGHT 12.8 lbs (w/o drives) SIZE Height: 9.8" (243 mm) Width: 7.0" (178 mm) Depth: 9.5" (241 mm)		
CONTROLLERS SoC; Dual LAN with 16bE w/Intel® I210 GRAPHICS Aspeed AST2400 BMC LED INDICATORS Status/Power, USB, LAN PUSH BUTTONS Power, Reset, Copy TEMPERATURE 0 - 60°C (32°F ~ 140°F) SMART FAN 1 x 12cm (12V DC) WEIGHT 12.8 lbs (w/o drives) SIZE Height: 9.8" (243 mm) Width: 7.0" (178 mm)	IPMI	Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and
LED INDICATORS Status/Power, USB, LAN PUSH BUTTONS Power, Reset, Copy TEMPERATURE 0 - 60°C (32°F ~ 140°F) SMART FAN 1 x 12cm (12V DC) WEIGHT 12.8 lbs (w/o drives) SIZE Height: 9.8" (243 mm) Width: 7.0" (178 mm)		244.2.4
PUSH BUTTONS Power, Reset, Copy TEMPERATURE 0 - 60°C (32°F ~ 140°F) SMART FAN 1 x 12cm (12V DC) WEIGHT 12.8 lbs (w/o drives) SIZE Height: 9.8" (243 mm) Width: 7.0" (178 mm)	GRAPHICS	Aspeed AST2400 BMC
TEMPERATURE 0 - 60°C (32°F ~ 140°F) SMART FAN 1x 12cm (12V DC) WEIGHT 12.8 lbs (w/o drives) SIZE Height: 9.8" (243 mm) Width: 7.0" (178 mm)	LED INDICATORS	Status/Power, USB, LAN
SMART FAN 1 x 12cm (12V DC) WEIGHT 12.8 lbs (w/o drives) SIZE Height: 9.8" (243 mm) Width: 7.0" (178 mm)	PUSH BUTTONS	Power, Reset, Copy
WEIGHT 12.8 lbs (w/o drives) SIZE Height: 9.8" (243 mm) Width: 7.0" (178 mm)	TEMPERATURE	0 - 60°C (32°F ~ 140°F)
SIZE Height: 9.8" (243 mm) Width: 7.0" (178 mm)	SMART FAN	1 x 12cm (12V DC)
Width: 7.0" (178 mm)	WEIGHT	12.8 lbs (w/o drives)
	SIZE	Width: 7.0" (178 mm)

All product specifications and data are subject to change without notice to improve reliability, function, design or otherwise.



- A Durable handle
- **B** Power Button
- C LED Indicators
- D LCD Display
- E Key Lock
- F ESC Button

- **G** Enter/Arrow Buttons
- **H** One-Touch Copy
- I USB (Type-C Ports)
- J SSD Drives
- K Optional 10G RJ-45 Ports
- L Optional External SAS2 Ports O RJ-45 1GbE(2)
- M Cooling Fan
- N DB15 VGAPort
- 0 10GbE SFP+ Ports
- P Optional 10G Ethernet Ports(4)
- R USB 3.0 (Type-A Ports)
- S IPMI Port
- T Power Connector
- *Thunderbolt 3 Ports available as option



All SecureNAS systems feature a durable, reliable, recessed handle for ease of transport without taking up valuable real estate.



Custom Transport Cases are the optimal solution for migrating or transporting large amounts of data safely and efficiently. **Enviromental test** lab certified.



All SecureNAS systems include a protective lockable door and a FIPS 140-2 certified encryption key to further protect both your physical NAS and data.









FCC CE COMPLIANCE - Designed/Assembled/Integrated/Tested in the USA using domestic and or foreign components. Made in the U.S.A.



Ciphertex-Protect® **Encryption Key**